

5.3. SYNTACTIC UTILITIES FOR CIF

```

/* These declarations have been automatically
generated by the cif file input/output function
generator. This file should be included in any
routines that call these functions */
typedef char cifstring[84];
/* to avoid array complications later */
#define MYLABELMAX 50
#define ATSITEUMAX 1000
typedef double atssiteutype [6];
#ifdef CIFVARDEC
cifstring errormes; /* an error message */
int errornum; /* an error number */
cifstring mylabel[50];
/*data_atom_site_aniso_label*/
atssiteutype atssiteu[1000];
/*data_atom_site_aniso_U*/
atssiteutype atssiteuesd[1000];
cifstring extmet;
/*data_refine_ls_extinction_method*/
double reftot [2]; /*data_reflms_number*/
double reftotesd [2];
#else
extern cifstring errormes; /* an error message */
extern int errornum; /* an error number */
extern cifstring mylabel[50];
/*data_atom_site_aniso_label*/
extern atssiteutype atssiteu[1000];
/*data_atom_site_aniso_U*/
extern atssiteutype atssiteuesd[1000];
extern cifstring extmet;
/*data_refine_ls_extinction_method*/
extern double reftot [2]; /*data_reflms_number*/
extern double reftotesd [2];
#endif

```

Fig. 5.3.7.5. Header file *cifvars.h* for a C application built by *BuildSiv* from the augmented DDL dictionary of Fig. 5.3.7.4.

5.3.7.2.3. Input to a C application program

When a DDL dictionary *dictfile* has been edited in accordance with the description above, the program *BuildSiv* may be run under a Unix-like operating system with a command of the form

```
BuildSiv dictfile ddlversion
```

where *ddlversion* takes the values '1' or '2' to indicate that a DDL1 or DDL2 parser is appropriate. If the option '-e' is given before *dictfile*, variable definitions and read capability for standard uncertainty values will be included as well. The name of the variable that will hold the standard uncertainty is the name given by the programmer with the string *esd* appended.

An object file *cifsiv.o* is produced together with a header file *cifvars.h*. Some source-code files are also produced as intermediate files in the lexical analysis and parse phases of the software build; these may be deleted. The object file must be linked against the other object files when the application program is compiled and references to the header files must be introduced (generally through C preprocessor `#include` directives) within the application code where access to the imported data structures is required.

Fig. 5.3.7.5 is an example of the header file *cifvars.h* built when *BuildSiv* reads the augmented dictionary of Fig. 5.3.7.4 with the '-e' option to interpret and store standard uncertainties.

The integer variable *errornum* stores a nonzero value if an error occurs in attempting to read a CIF, and an error message is stored in the character array *errormes*, indicating the nature of the problem. Errors generated by the input subroutine *cifsiv_* are not fatal to the parent application program, and will at worst discard the

```

/* A simple example application of the automatically
generated cifsiv_ function */
#include <stdio.h>
#include "cifvars.h"

main(int argc, char *argv[])
{
int i;
char filename[80];
char block[80];
printf("Please enter CIF file name: ");
scanf("%s", filename);
printf("Please enter data block name ");
printf("(without data_prepared): ");
scanf("%s", block);
errornum = 0;
cifsiv_(filename,block);
if(errornum != 0) /* an error, we have problems */
{
printf("An error occurred in reading the
CIF:\n");
printf("%s",errormes);
}
for(i=0;i<5;i++)
{
printf("Atom %d: %s %f %f\n", i, mylabel[i],
atsiteu[i][0], atsiteu[i][1]);
}
printf("Total reflections: %f\n", reftot[0]);
printf("Extinction method: %s\n", extmet);
}

```

Fig. 5.3.7.6. An example C program designed to read CIF data as tagged in the augmented DDL dictionary of Fig. 5.3.7.4.

particular loop block or data item affected. The parser operates by discarding CIF data upon encountering an error until it reaches an understandable set of input values. So, for example, if three numbers appear after an item name instead of one, the second two will be ignored after the error variables have been set, and parsing will continue. Similarly, if a serious error occurs within a loop, such as the appearance of an item name not matching an array variable, the entire loop is normally ignored. If a new packet of looped data exceeds the specified array limits, all further data in that loop are ignored.

The *cifsiv_* function has prototype

```
void cifsiv_(char* filename, char* blockname)
```

and requires pointers to character strings containing the name of the input file and the data-block code from which input is required.

A simple example C application illustrating the use of the *cifsiv_* subroutine is given in Fig. 5.3.7.6.

5.3.7.2.4. Input to a Fortran application program

A Fortran program can make use of the C input function generated by *BuildSiv* as long as the compiler used is capable of linking C and Fortran modules. For Fortran applications, the '-f' command-line option is used:

```
BuildSiv -f dictfile ddlversion
```

A C structure is defined for use within the *cifsiv_* subroutine and an identically constructed Fortran common block is built for use within Fortran routines. The first variable within the common block *must* be passed as an additional argument when the *cifsiv_* function is called. In the current implementation, that variable is

```

C The following common block corresponds to a
C structure defined in the C header, which is written
C to by routine 'cifsiv'. In order to correctly write
C to this common block, 'cifsiv' should be called
C with a *third* argument which will always be
C 'blockbeg'.
REAL BLOCKBEG
CHARACTER*84  ERRORMES
INTEGER ERRORNUM
CHARACTER*84  mylabel(50)
REAL*8  atrat(50)
REAL*8  atratesd(50)
REAL*8  atsiteu(6,500)
REAL*8  atsiteuesd(6,500)
CHARACTER*84  extmet
REAL*8  reftot(2)
REAL*8  reftotesd(2)
COMMON/CIFCMN/BLOCKBEG,ERRORMES,ERRORNUM,mylabel,
*atrat,atratesd,atsiteu,atsiteuesd,extmet,reftot,
*reftotesd

```

Fig. 5.3.7.7. Fortran include file forcif.inc for an application built by *BuildSiv* from the augmented DDL dictionary of Fig. 5.3.7.4.

```

PROGRAM FORGET
include 'forcif.inc'
call cifsiv("tbshort.cif","tbal03",blockbeg)
do i = 1,4
  write(*,*) mylabel(i), atsiteu(1,i),
*          atsiteu(2,i)
enddo
write(*,*) reftot(1)
write(*,*) extmet
end

```

Fig. 5.3.7.8. An example Fortran program designed to read CIF data as tagged in the augmented DDL dictionary of Fig. 5.3.7.4.

always called 'BLOCKBEG'. The input subroutine is thus called from within a Fortran program by a line of the type

```
CALL CIFSIV(FILE, BLOCK, BLOCKBEG)
```

where *FILE* and *BLOCK* are, respectively, the name of the input file and data block.

Fig. 5.3.7.7 is an example Fortran include file generated by *BuildSiv* and Fig. 5.3.7.8 is an example application incorporating this file. As with the C examples, the CIF data to be read are those specified in the dictionary augmented according to Fig. 5.3.7.4.

It may be noted that the C header file generated by the Fortran implementation of *BuildSiv* (and which is used directly by the C object file produced) is callable by any other C program or subroutine. The Fortran common block is represented by a C structure named *cifcmnptr*, so that the variable names are stored within that structure and must be addressed through the C \rightarrow operator. That is, an additional C routine compiled in with the Fortran example program of Fig. 5.3.7.7 would refer to the variable holding the value of the input `_refine_ls_extinction_method` as `(char *)cifcmnptr->extmet`.

5.3.8. Tools for mmCIF

The complex relationships between the components of a macromolecular structure at various levels of detail are richly described by the data names in the mmCIF dictionary, but their number and complexity demand more heavyweight tools for proper handling. Input/output for small-molecule or inorganic structures can

often be handled by a simple CIF parse and identification of the desired components of one or a few looped data structures. For macromolecules, multiple categories must be loaded simultaneously, and the integrity of relationships between items in the different categories must be properly maintained. For this reason, the most effective tools for mmCIF-based applications have high-level interactions with the mmCIF or related dictionaries, and necessarily involve more complex data manipulations.

In this section are discussed three software systems that are available for work with macromolecular structures: *CIFOBJ* and related libraries, which provide a long-established and complete application program interface (API) to dictionaries and data files; *OpenMMS*, an exciting development allowing abstract data representations (based on the mmCIF dictionary definitions) to be exchanged between applications using an intermediate middleware layer; and *mmLib*, which is a Python toolkit for biomolecular structure applications. These latter two may come closer to the area of domain-specific applications than most of the generic tools we have discussed in this chapter. However, they demonstrate how the abstract data model represented by the mmCIF dictionaries can effectively be imported into a diverse range of programming environments.

5.3.8.1. CIFOBJ and related libraries

Early in the development of the mmCIF dictionary, the Nucleic Acid Database at Rutgers University (Berman *et al.*, 1992) created a number of CIF libraries and utilities to underpin data-processing activities. Much of this development work was carried across when the curatorship of the Protein Data Bank was transferred to the Research Collaboratory for Structural Bioinformatics (RCSB; Berman *et al.*, 2002), and the software provides the engine for many of the robust and industrial-strength database operations of these organizations.

CIFLIB (Westbrook *et al.*, 1997) was an early class library, no longer supported, that was developed to provide an API to macromolecular CIF data files and to the associated dictionaries (Chapters 3.6 and 4.5) and underlying dictionary definition language (DDL2) files (Chapter 2.6).

The RCSB Protein Data Bank now distributes object-oriented parsing tools (*CIFPARSE_OBJ*; Tosic & Westbrook, 2000) which fully support CIF data files and their underlying metadata descriptions in dictionaries and DDL2 attribute sets, and a comprehensive library of access methods for data and dictionary objects at category and item level.

The information infrastructure of the Protein Data Bank, built upon these tools, is discussed in Chapter 5.5. All the software produced for this purpose is distributed with full source under an open-source licence, to promote the development of mmCIF tools and to encourage interoperability with other software environments.

5.3.8.2. OpenMMS

Object classes represent the first stage in abstracting related data components. By building structured software modules that can manage the small-scale interactions between data components, the programmer can write more succinct code to handle the interactions between much higher-level data constructs. An API then permits third parties to handle the larger-scale objects without any need to know the internal workings of the class library. The next logical step is to present a standard set of 'objects' representing complete logical entities to any programmer for 'plug-and-play' incorporation into new applications.