

5.6. *CBFlib*: AN ANSI C LIBRARY FOR MANIPULATING IMAGE DATA

```

/* Read and modify the template */

cbf_failnez (cbf_make_handle (&cbf))
in = fopen (template_name, "rb");

if (!in)
    exit (4);
cbf_failnez (cbf_read_template (cbf, in))

/* Wavelength */

wavelength =
    img_get_number (img, "WAVELENGTH");
if (wavelength)
    cbf_failnez (
        cbf_set_wavelength (cbf, wavelength))

/* Distance */

distance = img_get_number (img, "DISTANCE");
cbf_failnez (
    cbf_set_axis_setting (
        cbf, 0, "DETECTOR_Z", distance, 0))

/* Oscillation start and range */

axis = img_get_field (img, "OSCILLATION AXIS");

if (!axis)

    axis = "PHI";

osc_start = img_get_number (img, axis);
osc_range = img_get_number (img,
    "OSCILLATION RANGE");
cbf_failnez (
    cbf_set_axis_setting (
        cbf, 0, "GONIOMETER_PHI",
        osc_start, osc_range))

```

Fig. 5.6.5.1. An extract of program code for the conversion of image data to CBF format.

5.6.5. Example programs

The *CBFlib* API comes with example programs and sample templates. The example program *convert_image* reads either of the templates described in Section 5.6.4, *template_adscquantum4_2304x2304.cbf* and *template_mar345_2300x2300.cbf*, and uses the higher-level *CBFlib* routines to convert an image file to a CBF.

The example programs *makecbf* and *img2cif* read an image file from a MAR300, MAR345 or ADSC CCD detector and then use *CBFlib* to convert that image to CBF format (*makecbf*) or to either *imgCIF* or CBF format (*img2cif*). *makecbf* writes the CBF-format image to disk, reads it in again, and then compares it with the original. *img2cif* just writes the desired file without a verification pass. *makecbf* works only from files on disk, so that random input/output can be used. *img2cif* includes code to process files from stdin and to stdout. The example program *cif2cbf* copies an ASCII CIF to a binary CBF/*imgCIF* file.

5.6.5.1. *convert_image*

The program *convert_image* takes two arguments, *imagefile* and *cbffile*. These are the primary input and output. The detector type is extracted from the image file, converted to lower case and used to construct the name of a template CBF to use for the copy. The template file name is of the form *template_name_columnsxrows*. The program comes with *img.c* and *img.h* to read image files. It uses the *img_...* routines to extract data and metadata from the image and uses the higher-level *CBFlib* routines to populate the template. Fig. 5.6.5.1 is a portion of the

```

/* Make the _diffrn_frame_data category */
cbf_failnez(
    cbf_new_category          /* create the category */
        (cbf, "diffrn_frame_data"))
cbf_failnez(
    cbf_new_column           /* create the column */
        (cbf, "id"))
cbf_failnez(
    cbf_set_value            /* add data */
        (cbf, "frame_1"))
cbf_failnez(
    cbf_new_column           /* create next column */
        (cbf, "detector_element_id"))
cbf_failnez(
    cbf_set_integervalue     /* add data */
        (cbf, 1))
cbf_failnez(
    cbf_new_column           /* create the column */
        (cbf, "detector_id"))
cbf_failnez(
    cbf_set_value            /* add data */
        (cbf, detector_id))
cbf_failnez(
    cbf_new_column           /* create next column */
        (cbf, "array_id"))
cbf_failnez(
    cbf_set_value            /* add data */
        (cbf, "image_1"))
cbf_failnez(
    cbf_new_column           /* create next column */
        (cbf, "binary_id"))
cbf_failnez(
    cbf_set_integervalue     /* add data */
        (cbf, 1))

```

Fig. 5.6.5.2. Code fragment to illustrate the creation of the *DIFFRN_FRAME_DATA* category.

code that reads in the template and inserts the wavelength, the distance to the detector, and the oscillation start and range.

5.6.5.2. *makecbf*

makecbf is a good example of how to use many of the lower-level *CBFlib* functions. An example MAR345 image can be found at http://smb.slac.stanford.edu/~ellis/CBF_examples/mar345/mb_example_070.cbf. To run *makecbf* with the example image, type:

```
./bin/makecbf example.mar2300 test.cbf
```

The typical code fragment from *makecbf.c* shown in Fig. 5.6.5.2 creates the *DIFFRN_FRAME_DATA* category.

The program *img2cif* is an extended version of *makecbf* that allows the user to choose the details of the format of the output CBF. *img2cif* has the following command-line interface:

```
img2cif [-i input_image] [-o output_cif]
        [-c {p[acked] | c[anonical] | n[one]}]
        [-m {h[eaders] | n[oheders]}]
        [-d {d[igest] | n[odigest]}]
        [-e {b[ase64] | q[uoted-printable] |
            d[ecimal] | h[exadecimal] | o[ctal] | n[one]}]
        [-b {f[orward] | b[ackwards]}]
        [input_image] [output_cif]
```

-i takes the name of the input image file in MAR300, MAR345 or ADSC CCD detector format. If no *input_image* file is specified or is given as '-', an image is copied from stdin to a temporary file. *-o* takes the name of the output CIF (if BASE64 or quoted-printable encoding is used) or CBF (if no encoding is used). If no *output_cif* is specified or is given as '-', the output is written to stdout. *-c* specifies the compression scheme (packed, canonical or none; the default is packed). *-m* selects MIME (Freed &